



General

Provided equipment	User manual
--------------------	-------------

Physical

Cable length	1.22 m
Colour	Black
Depth	35.5 cm
Height	16 cm
Net weight	6 kg
Width	12 cm

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug standard	Schuko
Input voltage limits	140...300 V 230 V AC
Input voltage	230 V AC 1 phase

Output

Rated power in W	480 W
Maximum configurable power in W	480 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	2 Schuko
Output voltage	230 V AC 1 phase

Conformance

Product certifications	CE CB
Standards	EN/IEC 62040-1 EN/IEC 62040-2

CE

Equipment protection policy	Lifetime : 50000 euros
-----------------------------	------------------------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

Battery

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Liquid value	0
Battery voltage	12 V

Communication

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm

Surge

Surge energy rate	273 J
-------------------	-------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------